

EN-12275	CONNECTORS	UIAA-121				
<p>This representation of EN 12275 and UIAA 121 does not contain the full details of the test methods and requirements in these standards; it gives only a simplified pictorial presentation. For full details, EN 12275 and UIAA 121 should be consulted. © UIAA, Pit Schubert, Neville McMillan, 2004.</p> <p>The general term "Connectors" is used to include all types of karabiners and also quicklinks ("Maillon rapide").</p>						
<table style="width: 100%; border: none;"> <tr> <td style="width: 20%; text-align: center;"> <b>Type B (Basic)</b> Connector for normal use             </td> <td style="width: 20%; text-align: center;"> <b>Type D (directional)</b> Connector for Quickdraws             </td> <td style="width: 20%; text-align: center;"> <b>Type X (oval shape)</b> Connector for Aid climbing             </td> <td style="width: 20%; text-align: center;"> <b>Type H (HMS)</b> Connector for belaying             </td> </tr> </table>			<b>Type B (Basic)</b> Connector for normal use	<b>Type D (directional)</b> Connector for Quickdraws	<b>Type X (oval shape)</b> Connector for Aid climbing	<b>Type H (HMS)</b> Connector for belaying
<b>Type B (Basic)</b> Connector for normal use	<b>Type D (directional)</b> Connector for Quickdraws	<b>Type X (oval shape)</b> Connector for Aid climbing	<b>Type H (HMS)</b> Connector for belaying			
		<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>type K</td> <td>min. 21 mm</td> </tr> <tr> <td>all other types</td> <td>min. 15 mm</td> </tr> </table>	type K	min. 21 mm	all other types	min. 15 mm
type K	min. 21 mm					
all other types	min. 15 mm					
		<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;"><b>Gate opening force</b> (for all types)</td> </tr> <tr> <td style="text-align: center;">min. 5 N</td> <td style="text-align: center;">10 mm</td> </tr> </table>	<b>Gate opening force</b> (for all types)		min. 5 N	10 mm
<b>Gate opening force</b> (for all types)						
min. 5 N	10 mm					
<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;"><b>Type Q (Quick link)</b></td> </tr> <tr> <td colspan="2" style="text-align: center;">Connector for extra safety Quick link, "Maillon rapide"</td> </tr> </table>			<b>Type Q (Quick link)</b>		Connector for extra safety Quick link, "Maillon rapide"	
<b>Type Q (Quick link)</b>						
Connector for extra safety Quick link, "Maillon rapide"						

Designed by Georg Sajer

EN-12275	CONNECTORS	UIAA-121																
<b>Strength in main direction</b>		<b>Strength in transverse direction</b>																
<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>type K, Q</td> <td>25 kN</td> </tr> <tr> <td>type X</td> <td>18 kN</td> </tr> <tr> <td>all other types</td> <td>20 kN</td> </tr> </table>		type K, Q	25 kN	type X	18 kN	all other types	20 kN	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>type Q</td> <td>10 kN</td> </tr> <tr> <td>type B, H, K, X</td> <td>7 kN</td> </tr> <tr> <td>typ D</td> <td>--</td> </tr> </table>	type Q	10 kN	type B, H, K, X	7 kN	typ D	--				
type K, Q	25 kN																	
type X	18 kN																	
all other types	20 kN																	
type Q	10 kN																	
type B, H, K, X	7 kN																	
typ D	--																	
<b>Gate-open strength</b>		<b>Marking of strength (in kN)</b>																
<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>type B, D</td> <td>7 kN</td> </tr> <tr> <td>type H</td> <td>6 kN</td> </tr> <tr> <td>type X</td> <td>5 kN</td> </tr> <tr> <td>type K, Q</td> <td>--</td> </tr> </table>		type B, D	7 kN	type H	6 kN	type X	5 kN	type K, Q	--	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">strength</td> </tr> <tr> <td>xx</td> <td>in main direction</td> </tr> <tr> <td>yy</td> <td>in transverse direction</td> </tr> <tr> <td>zz</td> <td>gate-open</td> </tr> </table>	strength		xx	in main direction	yy	in transverse direction	zz	gate-open
type B, D	7 kN																	
type H	6 kN																	
type X	5 kN																	
type K, Q	--																	
strength																		
xx	in main direction																	
yy	in transverse direction																	
zz	gate-open																	
<b>Additional requirements of UIAA 121 only for type K (Klettersteig, "via ferrata")</b>																		
<b>Gate-open strength</b>		<b>Strength over an edge</b>																
<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>min. 8 kN</td> </tr> </table>		min. 8 kN	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>min. 8 kN</td> </tr> </table>	min. 8 kN														
min. 8 kN																		
min. 8 kN																		

Designed by Georg Sajer